

ALL-IN-ONE PROCESSORS

COMBI 25/30 FLEXO-WATER



MAIN FEATURES

Combination “all in one” processor for flexo water plates

- Independent processing sections
- Compatible with analogue and digital plates
- Fastening section on a table with permanent sticky plate
- Washout of the whole plate surface through an orbital movement of the brush segment
- Independent movement of the table during the wash out cycle
- Automatic rinsing and pre-drying of the plate
- Main exposure and finishing sections equipped with LEDs indicating the status of each lamp
- Intuitive user-friendly HMI touch screen controlling all the steps of the process
- Temperature control of the wash out solution, dryer and main exposure bed
- Detergent dosing pump managed by the computer
- Filtration system
- Remote connection possibility
- Compressed air and water supply required



TECHNICAL DATA

25/30	MODEL
635x762 mm 25"x30"	Max. Plate Dimensions
128x212x146	Machine Dimension WxDxH cm
128x109x118	Recycle Dimension WxDxH cm
740	Machine Weight kg
200	Recycle Weight kg
400V 3PH+N+GND 50/60Hz 230V 3PH+GND 50/60Hz	Power Supply
11,5	Power kW
80	Tank Capacity (l)
23	Filter Capacity (l)
1800	Filtering Area (cm ²)
450	Air Consumption (l/min)
6	Pressure (bar)
13x60W 10R L. 1200 mm	Exposure UVA Lamps
12x60W 10R L. 900 mm	Post-Exposure UVA Lamps
11x30W L. 900 mm	Exposure UVC Lamps

THE IMAGES IN THIS DOCUMENT ARE PROVIDED FOR ILLUSTRATIVE PURPOSES.
WE RESERVE THE RIGHT TO MAKE CHANGES AND IMPROVEMENTS TO ANY PRODUCT DESCRIBED HEREIN WITHOUT NOTICE.

WWW.AGIGRAPHICS.COM