

## EXPOSURE UNITS

# EDF FLEXO-WATER



### MAIN FEATURES

- Combined exposure, dryer and light finishing unit
- Intuitive user-friendly HMI touch screen controlling all the steps of the process
- Main exposure equipped with light integrator and airflow system for lamps cooling
- Main exposure and finishing sections equipped with LEDs indicating the status of each lamp
- Drying section consisting of 4 drying drawers with independent timers
- Light finishing section with UVA and UVC lamps
- Dedicated exhaust system
- Remote connection possibility

### Optional

- Main exposure with cooled bed





## TECHNICAL DATA

<b>36/47</b>	<b>42/60</b>	<b>52/80</b>	<b>MODEL</b>
920x1240 mm 36"x48"	1070x1530 mm 42"x60"	1320 x 2030 mm 52"x80"	Max. Plate Dimensions
186x162x109	220x190x123	315x190x120	Dimension WxDxH cm
650	800	900	Weight kg
230V 50/60Hz 3PH+GND 400V 50/60Hz 3PH+N+GND			Power Supply
12	13,5	15	Power kW
21x80W 10R L.1500 mm	33x60W 10R L.1200 mm	42x80W 10R L.1500 mm	Exposure UVA Lamps
17x80W 10R L.1500 mm	28x60W 10R L.1200 mm	36x80W 10R L.1500 mm	Post-Exposure UVA Lamps
16x60/95W L.1500 mm	27x36W L.1200 mm	35x60/95W L.1500 mm	Exposure UVC Lamps

THE IMAGES IN THIS DOCUMENT ARE PROVIDED FOR ILLUSTRATIVE PURPOSES.  
WE RESERVE THE RIGHT TO MAKE CHANGES AND IMPROVEMENTS TO ANY PRODUCT DESCRIBED HEREIN WITHOUT NOTICE.

[WWW.AGIGRAPHICS.COM](http://WWW.AGIGRAPHICS.COM)