### **EXPOSURE UNITS**

# **EDF** LETTERPRESS



#### **MAIN FEATURES**

- Combined exposure and dryer
- Intuitive user-friendly HMI touch screen controlling all the steps of the process
- Main exposure equipped with light integrator and airflow system for lamps cooling
- Main exposure equipped with LEDs indicating the status of each lamp
- Drying section consisting of 4 drying drawers with independent timers
- Remote connection possibility

Optional

- Main exposure with cooled bed
- Separate UVA post exposure section



WWW.AGIGRAPHICS.COM

# TECHNICAL DATA

36/47	MODEL
920x1240 mm 36"x48"	Max. Plate Dimensions
186x162x109	Dimension WxDxH cm
650	Weight kg
400V 3PH+N+GND 50/60Hz 230V 3PH+GND 50/60 Hz	Power Supply
10	Power kW
21x80W 10R L.1500 mm	Exposure UVA Lamps

THE IMAGES IN THIS DOCUMENT ARE PROVIDED FOR ILLUSTRATIVE PURPOSES. WE RESERVE THE RIGHT TO MAKE CHANGES AND IMPROVEMENTS TO ANY PRODUCT DESCRIBED HEREIN WITHOUT NOTICE.

## WWW.AGIGRAPHICS.COM