

COMBINATION PROCESSORS

POLYMER 25/30 FLEXO-WATER



MAIN FEATURES

Combination processor for flexo water plates

- Independent processing sections
- Compatible with analogue and digital plates
- Fastening section on a table with permanent sticky plate
- Washout of the whole plate surface through an orbital movement of the brush segment
- Independent movement of the table during the wash out cycle
- Main exposure and finishing sections equipped with LEDs indicating the status of each lamp
- Intuitive user-friendly HMI touch screen controlling all the steps of the process
- Temperature control of the wash out solution and dryer
- Filtration system
- Remote connection possibility
- Compressed air and water supply required



AGI
Attrezzature Grafiche Italia

WWW.AGIGRAPHICS.COM

TECHNICAL DATA

25/30	MODEL
635x762 mm 25"x30"	Max. Plate Dimensions
129x120x124	Machine Dimension WxDxH cm
112x75x110	Recycle Dimension WxDxH cm
470	Machine Weight kg
180	Recycle Weight kg
400V 50/60Hz 3PH+N+GND 230V 50/60Hz 3PH+GND	Power Supply
10	Power kW
95	Tank Capacity (l)
23	Filter Capacity (l)
1800	Filtering Area (cm ²)
50	Air Consumption (l/min)
6	Pressure (bar)
13x60W 10R L. 1200 mm	Exposure UVA Lamps
11x30W L.900 mm	Exposure UVC Lamps
12x60W 10R L. 900 mm	Post-Exposure UVA Lamps